





COLORIS



ELECTRIC SYSTEM	Drive Unit	Bosch Performance Line, 36 V mid motor 250 W - 63 Nm
	Battery	Bosch Powerpack 400 Wh
	Charging Time	2h45:100%
	Average Range**	60/160 km
	Display	Intuvia LCD central multifonctions with remote control, removable
	Sensors	3 sensors (Cadence, Speed and Tork)
	Support Modes	5 riding modes + Walk assistance / Assistance until 25 km/h
FRAME		Frame Solex Trekking, Alloy 6061 T6
FORK		Suntour NCX
DRIVETRAIN	Type, ratio	18 x 11/36 teeth
	Derailleur / Speeds	Shimano Deore 10 Speeds
	Shifter	Shimano Deore
BRAKES		Hydraulic Discs Shimano AM365 160 mm Front and Rear
HANDLE BAR SET	Handle Bar	Sport 660 mm x 31,8 mm
	Stem	Ahead black 90 mm +/- 6°
	Grips	Sport Black-Red
	Head Set	Semi integrated Ahead
WHEELS	Rims	Mach1 Traxx
	Hub Front/Rear	Black Alloy
	Tires	Schwalbe Energizer+ Tour 28x1,50
	Inner Tubes	Schwalbe AV19, valve Schrader
SADDLE	Saddle	Selle Royal® Respiro
	Seat Post	Suspended 30,9x350 mm black
LIGHTS	Front Light	Integrated Spanninga LED
	Rear Light	Trelock Duoflat LED
ACCESSORIES	Front Carrier	-
	Back Carrier	Alloy Red
	Kick Stand	Lateral Rear
	Frame Lock	-
PROTECTION	Mudguards	SKS
	Chain Guard	SKS <sup>™</sup> half chain guard black
MODELS	Colors	Black-Red
	Size	M:48 cm/L:53 cm
	Weight***	24 kg
	Warranty	Frame 5 years, Drive and Battery 2 years

<sup>\*</sup> Battery ranges are provided for guidance only. They are measured following a test protocol defined by Easybike Group or provided by the battery manufacturer. The main factors leading to loss of battery range are: headwind, positive height difference, temperature less than 15°C, under-inflated tyres, user weight greater than the nominal weight defined for our tests (70 kg), wrongly adjusted bicycle, incorrect use of gens.

In order to meet its customers' requirements as much as possible, MATRA reserves the right to modify the characteristics of its products at any time, without notice. Document, information and photos non contractual. Products sold may vary by country. Please contact your authorised Easybike Group distributor.